



BASE

Low carbon steel single side plate and box end fabrication welded in proper sequence with suitable rod to reduce stress.

PITMAN

Ribbed open back cast steel design for minimizing weight while maintaining strength.

SHAFT

SAE4140 forged steel shaft is precision machined for eccentricity and bearing journals.

BEARINGS

Spherical roller self aligning type with straight bore pitman bearings and tapered bore main bearings. Pillow block housing mounted in saddle blocks for maximum support and precise alignment to reduce loading on shaft and bearings. The self-aligning bearings prevent side movement of the pitman assembly, thus eliminating the need for side thrust assemblies.

NOTE: Specifications are subject to change without notice.

LUBRICATION

Grease system or optional oil circulation system.

FLYWHEELS

Ductile iron 50" diameter standard flywheels. Drive flywheel has 10-5V grooves. Optional diameters are available.

TOGGLE

Ductile iron 26" standard length toggle plate with other lengths available for specialized applications. Alloy cast steel toggle seat.

SIDE LINERS

Abrasion resistant steel key and heel plates protect crushing chamber.

JAW DIES

Manganese steel jaw dies with machined back available in various profiles to meet all applications.

ADJUSTMENT

Shim adjust with hydraulic positioning for easy setting of crusher.

CRUSHER DATA:

Jaw Opening (Gap): 28" (711mm)

Jaw Width: 54" (1372mm)

Moving Jaw, Overall Depth: 60 1/2" (1537mm)

Stationary Jaw, Overall Depth: 56" (1422mm)

Weight: 51,000lb (23,154kg)

Power Required (HP): 150-200 Electric, 190-250 Diesel

RPM: 250 Maximum

Stroke: 1 1/4"

PEAK to PEAK CLOSED SIDE SETTING

Approximate Capacity

Crusher Setting

(Close of Stroke)	inches	3"	3 1/2"	4"	5"	6"
	mm	76	89	102	127	152
* Tons per Hour		213	241	268	323	378
mt/h		194	219	195	293	342

Test Sieve	APPROXIMATE GRADATIONS AT PEAK TO PEAK CLOSED SIDE SETTINGS														Test Sieve
	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	5"	6"	7"	8"	Sizes (mm)	
Sizes (in.)	19	25.4	31.8	38.1	50.8	63.5	76.2	89.1	102	127	152	178	203	Sizes (mm)	
12											100	98	95	305	
10										100	97	95	90	254	
8									100	96	92	85	75	203	
7	Values Are Percent Passing								100	97	92	85	78	65	178
6							100	98	93	85	74	65	53	152	
5						100	97	95	85	73	62	52	40	127	
4					100	96	90	85	70	58	45	38	28	102	
3				100	93	85	75	65	50	38	32	27	23	76.2	
2 1/2			100	95	85	73	62	52	38	31	24	22	17	63.5	
2		100	96	85	70	55	47	39	28	24	20	17	13	50.8	
1 1/2	100	93	85	67	49	39	33	27	21	18	15	13	10	38.1	
1 1/4	96	85	73	55	39	31	27	23	17	15	13	10	8	31.8	
1	85	69	55	40	29	24	20	17	14	12	10	8	6	25.4	
3/4	66	49	39	28	21	18	15	13	11	9	8	6	5	19.0	
1/2	41	29	24	19	14	12	10	9	7	6	6	5	4	12.7	
3/8	28	21	18	14	11	9	8	7	5	5	5	4	3	9.53	
1/4	18	14	12	10	7	7	6	5	4	4	4	3	2	6.35	
#4	12	10	9	7	5	5	4	4	3	3	3	2	1	#4	
#8	6	6	5	5	4	4	3	3	2	2	2	1	0.5	#8	

* Based on material weighing 2700 lb per cubic yard. Capacity may vary as much as ±25%.

NOTE: Specifications are subject to change without notice.

FOR MORE INFORMATION CALL 1-800-542-9311 AND ASK FOR A PIONEER EQUIPMENT SPECIALIST. YOUR AUTHORIZED DEALER:

KOLBERG-PIONEER, INC.

700 W. 21st Street - P.O. Box 20
Yankton, South Dakota 57078

Phone: (605) 665-8771 - FAX: (605) 665-8858

mail@kolbergpioneer.com - www.kolbergpioneer.com

Because Kolberg-Pioneer, Inc. may use in its catalog & literature, field photographs of its products which may have been modified by the owners, products furnished by Kolberg-Pioneer, Inc. may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of Kolberg-Pioneer, Inc. are subject to the provisions of its standard warranty. Kolberg-Pioneer, Inc. does not warrant or represent that its products meet any federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety, pollution, electrical wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the area and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and the use to which the product is put. A safety study should be made by the user of the application, and, if required additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.