


Conveyor Frame:

24" Deep Lattice Frame with 3" x 3" x 1/4" chord angles

Idlers:

All standard idlers are CEMA B – 5" diameter

- 35 degree troughing idlers (3 roll) on 4' spacing
- 20 degree idlers (3 roll) at feed point close spacing
- Flat steel return idlers (single roll) on 10' spacing

Undercarriage:

Manual telescoping pin lock. Axle – single axle with single 11:00 – 22.5 tires on swivel wheel boxes

Receiving Trough:

5' 6" long with adjustable rubber flashing.

Belt Drive:

- Head end drive
- 250 TPH capacity (100 pcf material).
- 10 Hp - 3/60/230-460 TEFC electric motor
- Class I TA2115 Dodge shaft mount reducer w/backstop
- V-belt, motor mounts and guards
- 16" dia., 3/8" grooved head
- 14" dia. steel wing tail
- 12" Screw take-up

Belt:

2 ply 220 PIW, 1/8" x 1/16" cover with mechanical fasteners.

Belt Cleaner (Optional):

Martin belt cleaner on head pulley of conveyor.

Paint:

One coat of primer, finish coat of Beige acrylic.

Physical / Operating Characteristics:

Overall Length:..... 50'
 Travel Length; kingpin to tail..... 49'-2"
 Travel Height..... 12'-2"
 Travel Width..... 11'-10"
 Feed Height 5'-2"
 Discharge Height..... 17'-5"
 Travel Weight (kingpin)..... 2,700 lbs
 Travel Weight (axle) 7,800 lbs

Stockpile Capacities (100 pcf material):

Conical Pile..... 474 ton / 351 yd³
 1° Pile Segment 16 ton / 12 yd³
 90° Pile 1,956 ton / 1,449 yd³
 180° Pile 3,438 ton / 2,547 yd³

Options:

- Radial Hopper
- AR Liners
- Anchor Pivot
- Undercarriage Lift Cylinder
- 7.5 Hp electric/hydraulic power pack
- Power Travel
- Pintle hitch
- Impact Idlers (3)
- Rubber disc return idlers
- CEMA C idlers
- 3 ply, 330 PIW belting
- Vulcanized belt splice
- King Pin*
- Dual Tires*
- Travel Lights*
- Air Brakes*

*Recommended for Highway Portability



700 W. 21st Street – P.O. Box 20
 Yankton, South Dakota 57078
 Phone: (605) 665-8771
 FAX: (605) 665-8858
mail@kpijci.com
www.kpijci.com

NOTE: Specifications are subject to change without notice.

Because KPI-JCI may use in its catalog & literature, field photographs of its products which may have been modified by the owners, products furnished by KPI-JCI may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of KPI-JCI are subject to the provisions of its standard warranty. KPI-JCI does not warrant or represent that its product meet and federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety, pollution, electrical wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the areas and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and the use to which the product is put. A safety study should be made by the user of the application, and, if required additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.