

80' [24.4m] Stackers

Radial Stacker



Frame

Heavy-duty lattice type

Idlers

- All standard idlers are CEMA B – 5" [127mm] diameter
 - 35 degree troughing idlers on 4' [1.2m] spacing
 - 20 degree idlers at feed point close spacing
 - Flat steel return idlers on 10' [3m] spacing

Undercarriage

- Manual telescoping pin lock
- Axle – single axle with single 11:00 – 22.5 tires on swivel wheel boxes (**42" [1,067mm] belt width includes dual tires**)

Receiving Trough

- 5' 6" [1.7m] long with adjustable rubber flashing

Belt Drive

- Head end drive
- 3/60/230-460 TEFC electric motor
- Class I Dodge shaft mount reducer with backstop
- V-belt, motor mounts and guards
- 3/8" [9.5mm] grooved, head pulley
- Steel wing tail pulley
- 18" [457mm] Screw take-up
- Belt Speed - 350 FPM [1.7 MPS]

Conveyor Specifications

Belt Width		Frame Depth		Capacity*		Drive		Reducer	Head Pulley		Snub Pulley		Tail Pulley	
in	mm	in	mm	STPH	MTPH	hp	kW		in	mm	in	mm	in	mm
24	610	30	762	250	227	10	7.5	TA2115	16	406	-	-	14	356
30	762	30	762	500	454	20	14.9	TA3203	16	406	-	-	14	356
36	914	30	762	750	680	25	18.6	TA4207	18	457	-	-	16	406
42	1,067	36	914	1000	907	40	29.8	TA5215	18	457	16	406	16	406

*Capacity based on 100 PCF [1.3 T/M³] Material

Belt:

- 2 ply 220 PIW, 1/8" x 1/16" [3.2mm x 1.6mm] covers with mechanical fasteners

Options:

- Belt Cleaner
- Radial Hopper
- Rock Box Hopper
- Oversized Rock Box Hopper
- Hydraulic Belt Drive
- AR Liners
- Anchor Pivot
- Undercarriage Lift Cylinder
- 7.5hp [5.6 kW] electric / hydraulic power pack
- Power Travel - 2hp [1.5 kW] electric
- Power Travel - Hydraulic
- Pintle Hitch
- CEMA C Idlers
- Impact Idlers (3)
- Rubber Disc Return Idlers
- 3 ply, 330 PIW belting
- Vulcanized belt splice
- Manual Top Fold* (head end only)
- Hydraulic Top Fold (head end only)
- Gullwing Axle
- Planetary Drive for Gullwing Axle
- Hydraulic Axle Raise
- King Pin*
- Dual Tires*
- Travel Lights*
- Air Brakes*

*Recommended for Highway Portability

Physical and Operating Characteristics

Dimension	Standard	Metric
Conveyor Length	80'	24.4m
Travel Length (King pin to tail)	54'-11"	16.7m
Travel Height	13'	3.9m
Travel Width	11'-11"	3.6m
Feed Height	5'-2"	1.6m
Maximum Discharge Height	26'-11"	8.2m
Minimum Discharge Height	13'-5"	4.1m

Weights

Belt Width		Travel Weight (King Pin)		Travel Weight (Axle)	
Inches	MM	lbs	kg	lbs	kg
24	610	2,400	1,089	12,700	5,761
30	762	3,200	1,451	14,900	6,758
36	914	5,300	2,404	16,800	7,620
42	1,067	5,500	2,495	19,200	8,709

Stockpile Capacities

Pile Type	Short Tons	Metric Tons
Conical Pile	1,700	1,542
90° Pile	7,261	6,587
180° Pile	12,822	11,632
270° Pile	18,382	16,676



Kolberg-Pioneer, Inc.
700 West 21st Street,
Yankton, SD 57078
1 (800) 542-9311
mail@kpijci.com
www.kpijci.com

NOTE: CONSULT FACTORY FOR EXACT DIMENSIONS, specifications are subject to change without notice.

Because Kolberg-Pioneer, Inc., Johnson Crushers International, Inc. and Astec Mobile Screens, Inc. may use in their catalog and literature, field photographs of their products which may have been modified by the owners, products furnished by Kolberg-Pioneer, Inc., Johnson Crushers International, Inc. and Astec Mobile Screens, Inc. do not warrant or represent that their products meet any federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety, pollution, electrical wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the area and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and how the product is used. A safety study should be made by the user of the application, and, if required additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.

Rev: 3/19